




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : H04B 3/23</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/34353 (43) International Publication Date: 6 August 1998 (06.08.98)</p>
<p>(21) International Application Number: PCT/SE98/00060 (22) International Filing Date: 15 January 1998 (15.01.98) (30) Priority Data: 08/792,866 31 January 1997 (31.01.97) US (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventors: DREYFERT, Torkel; Gökärtsvägen 83, S-187 51 Täby (SE). ORTOLANIS, Petros; Anna Strasse 56, D-52062 Aachen (DE). (74) Agent: ERICSSON RADIO SYSTEMS AB; Common Patent Dept., S-164 80 Stockholm (SE).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>

(54) Title: DYNAMIC ECHO CANCELLER AND PARAMETER SELECTION IN TELEPHONY SYSTEMS



(57) Abstract

An echo canceller pool configuration (110) is provided that allows a user (102) to predetermine and individualize the echo cancellation parameter settings (Fig. 8) for any echo canceller in the pool, based on prior knowledge of the echo path characteristics of the specific transmission route to be used for an ensuing call. The echo canceller with the individualized parameter settings is then switched into that route for the duration of the call. For example, at call setup, once a trunk route has been identified that will be used to complete the call, a "flag" is retrieved that is associated with that specific route. That "flag" identifies specific echo canceller parameter settings to be used for that route. Those parameter settings are downloaded to the echo canceller device selected from the pool (110), and that device is then switched into the specific trunk involved.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DYNAMIC ECHO CANCELLER AND PARAMETER SELECTION IN TELEPHONY SYSTEMS

5 BACKGROUND OF THE INVENTION

Technical Field of the Invention

The present invention relates in general to the telecommunications field and, in particular, to the dynamic selection of echo cancellers and echo cancellation parameters in telephony systems.

10 Description of Related Art

Speech quality has become a highly competitive factor in marketing telephony systems. Echo, which is a phenomenon typically caused by imperfect impedance matching of network transmission sections, has a significant impact on the overall speech quality of telephony systems. Specifically, the primary cause of echo in many telephony systems is the impedance mismatch between connected two-wire and four-wire network transmission sections.

For example, FIGURE 1 is a schematic block diagram that illustrates how echo can occur in a Public Switched Telephone Network (PSTN). As shown in a typical arrangement, a PSTN subscriber's telephone 1 is connected by a two-wire transmission line to a hybrid interface circuit 1'. The hybrid circuit (1') functions to convert from the telephone's two-wire access line to the PSTN's four-wire transmission line (needed for two-way communications). Similarly, a second PSTN subscriber's telephone 2 is connected by a two-wire transmission line to a second hybrid circuit 2', which also makes the two-wire to four-wire conversion. Since each hybrid is a non-ideal circuit, an impedance mismatch occurs at each hybrid (1', 2') between the two-wire lines and four-wire line, which reflects a portion of the incoming speech energy from the four-wire line back to each of the respective subscriber's phones (1, 2). This reflected speech energy, or echo, is typically a distorted and delayed replica of the outgoing speech reflected from the other subscriber side. In FIGURE 1, the respective energy reflections (echos) for subscriber's 1 and 2 are illustrated by the dotted arrows 1" and 2".

- 2 -

In general, as long as the reflected energy transmission delay time is relatively short (e.g., ≤ 25 ms), the reflected speech energy is normally not perceived to be annoying. However, when the delay is increased beyond 25 ms, the reflected energy is normally perceived as an annoying "talker echo". The higher the delay time, the more annoying and/or confusing the echo becomes. For example, FIGURE 2 is a graph that illustrates the required echo attenuation needed as a function of transmission delay time. As shown, the total echo return loss (ERL) can be plotted as a function of delay time to generate an echo tolerance curve. As the delay increases above 25 ms, echo control procedures are required.

In summary, echos become more annoying as network transmission path delay times are increased. Such transmission path delays can be introduced in a number of ways, such as by propagating speech signals over long distances, or by the process of coding transmitted speech signals. For example, significant propagation delays occur during satellite communication transmissions for intra- and intercontinental calls. A geostationary satellite (due to its substantial distance from the earth) typically introduces a one-way transmission path delay of about 260 ms, or a total (round-trip) echo path delay of about 520 ms. FIGURE 3 is a diagram that shows a satellite communications link and illustrates how such a system introduces a significant transmission (echo) path delay.

Digital cellular communications systems also introduce significant echo path delays. For example, the speech and channel coding used for fault tolerance in digital cellular communications system radio transmissions introduces a one-way transmission path delay of about 100 ms, as blocks of speech samples are transmitted and re-transmitted over the air interface. FIGURE 4 is a diagram that shows a digital cellular communications system and illustrates such an echo path delay.

Echo cancellers are electronic devices that are used to suppress the effects of echos in telephony systems. For example, for connections with long transmission delays between subscribers (e.g., FIG. 1), two echo cancellers are typically used (one on either side of the transmission path that causes the delay). For long distance satellite communications systems (e.g., FIG. 3) that link to PSTNs, an echo canceller is typically located at each of the gateway switches or transit nodes (e.g.,

- 3 -

at the international switching centers or ISCs) associated with each local exchange, but "facing" the respective PSTN. In a digital cellular communications system (e.g., FIG. 4) that links to a PSTN, an echo canceller is typically located at a mobile services switching center (MSC) and also "facing" the PSTN.

5 FIGURE 5 is a simplified schematic block diagram that illustrates two echo canceller configurations that can be used in existing telephony systems: (1) trunk echo cancellers, and (2) echo cancellers in a pool (ECP) configuration. In the examples illustrated by FIGURE 5, three trunk lines (2, 4, 8) are shown, each of which connects a PSTN (11) transmission line to a digital cellular system 12 via a
10 group switch (e.g., part of an MSC) 10 for speech communications therebetween. Group switch 10 can be a component of a digital switching system, such as, for example, an AXE 10 digital switching system manufactured by Ericsson Telecom AB. An echo canceller device 14 is physically connected to trunk line 2. The electrical parameter settings for trunk echo canceller 14 are controlled by echo
15 canceller control circuit 16. An exchange terminal circuit 18 is connected between trunk echo canceller 14 and group switch 10.

 An echo canceller pool 30 is associated with group switch 10. A plurality of echo cancellers are maintained in the pool (30) to form a part of the trunk signalling subsystem (TSS) of the digital switching system. A conventional echo
20 canceller pool 30 can be, for example, an ECP 101 product, which is manufactured by Ericsson Telecom AB. As shown, no trunk echo canceller is physically located at trunk 8. Instead, when a call is initiated between the PSTN (11) and the digital cellular system (12), the traffic control subsystem (TCS) of the digital switching system selects one of the echo cancellers in the pool (30) and directs switch 10 to
25 route the connection through the selected echo canceller for the duration of the call. In that way, a more efficient use of echo cancellers is possible and thus reduces the total number of echo cancellers needed, as compared to prior trunk echo canceller configurations. Also, there is increased reliability over the prior systems, because there are always some echo cancellers available in the pool, which can be used in
30 the event one or more of the other echo cancellers develops a fault.

- 4 -

Although the use of echo canceller pool configurations has increased the flexibility and reliability of existing telephony systems, a significant problem still exists with respect to echo cancellation. Specifically, all of the echo cancellers in each existing pool are configured with the same cancellation parameters, which
5 significantly limits the flexibility of existing telephony systems.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide individualized echo cancellation parameter settings for specific echo cancellers in a pool.

10 It is also an object of the present invention to provide a dedicated pool of echo cancellers for certain high priority transmission paths in a telephony system.

It is another object of the present invention to customize echo cancellers for specific trunk routes in a telephony system.

15 It is yet another object of the present invention to create a congestion-free pool of echo cancellation devices.

It is a further object of the present invention to minimize echo and thereby improve the speech quality of telephony systems.

In accordance with the present invention, the foregoing and other objects are achieved by a method and apparatus, in which an echo canceller pool configuration
20 is provided that allows a user to predetermine and individualize the echo cancellation parameter settings for any echo canceller in the pool, based on prior knowledge of the echo path characteristics of the specific transmission route to be used for an ensuing call. The echo canceller with the individualized parameter settings is then switched into that route for the duration of the call. For example, at call setup, once
25 a trunk route has been identified that will be used to complete the call, a traffic control system retrieves a "flag" from a memory address associated with that specific route. That "flag" identifies specific echo canceller parameter settings to be used for that route. Those parameter settings are downloaded to the echo canceller device selected from the pool, and that device is then inserted into the specific trunk
30 involved.

- 5 -

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be had by reference to the following detailed description when taken in conjunction with the accompanying drawings wherein:

5 FIGURE 1 is a schematic block diagram that illustrates how echo can occur in a Public Switched Telephone Network;

FIGURE 2 is a graph that illustrates the required echo attenuation needed as a function of transmission delay time;

10 FIGURE 3 is a diagram that shows a satellite communications link and illustrates how such a system introduces a significant transmission (echo) path delay;

FIGURE 4 is a diagram that shows a digital cellular communications system and illustrates an echo path delay;

FIGURE 5 is a simplified schematic block diagram that illustrates two echo canceller configurations that can be used in existing telephony systems;

15 FIGURE 6 is a schematic block diagram of an exemplary cellular communications system that may be used for dynamically selecting echo cancellers and echo cancellation parameter settings, in accordance with a preferred embodiment of the present invention;

20 FIGURE 7 is a flow chart that illustrates a method that can be used to implement dynamic selection of an echo canceller and individualized echo cancellation parameters for a specific route, in accordance with the preferred embodiment of the present invention; and

25 FIGURE 8 is a table that shows exemplary echo canceller parameters and values that can be set for a trunk route, in accordance with the preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

The preferred embodiment of the present invention and its advantages are best understood by referring to FIGURES 1-8 of the drawings, like numerals being
30 used for like and corresponding parts of the various drawings.

- 6 -

Essentially, an echo canceller pool configuration is provided that allows a user to predetermine and individualize the echo cancellation parameter settings for any echo canceller in the pool, based on prior knowledge of the echo path characteristics of the specific transmission route to be used for an upcoming call.

5 The echo canceller with the individualized parameter settings is then switched into that route for the duration of the call. For example, at call setup, once a trunk route has been identified that will be used to complete the call, a traffic control system retrieves a "flag" from a memory address associated with that specific route. That "flag" includes specific echo canceller parameter settings for that route. Those

10 parameter settings are downloaded to the echo canceller device selected from the pool, and that device is then inserted into the specific trunk involved.

Specifically, FIGURE 6 is a schematic block diagram of an exemplary cellular communications system that may be used for dynamically selecting echo cancellers and echo cancellation parameter settings, in accordance with a preferred

15 embodiment of the present invention. System 100 can include a plurality of mobile terminals, one or more base station transceivers, and one or more MSCs or gateway MSCs associated with the base station transceivers. Each gateway MSC can have an associated echo canceller pool. However, since only one routing connection between users needs to be shown to adequately describe the invention, the system

20 shown in FIGURE 6 includes a mobile terminal (e.g., cellular phone) 102, a base station transceiver 104 for communicating with mobile terminal 102 via the air interface, a gateway MSC 106 connected to base station transceiver 104, and an echo canceller pool 110 connected to gateway MSC 106.

In this embodiment, a traffic control subsystem 108 is associated with

25 gateway MSC 106 and echo canceller pool 110. The traffic control subsystem can be implemented entirely in software and contains the traffic-handling and traffic-control functions of the switch involved. The software functions of the traffic control subsystem can be implemented under the control of a digital processor (not explicitly shown) associated with the gateway MSC. The gateway MSC (106) is

30 connected via a transmission line to an exchange terminal circuit 111, and a trunk line to a remote switch 112 (e.g., a switch in a PSTN exchange).

- 7 -

As shown, the gateway MSC (106) can connect the base station transceiver (104) and the echo cancellers in the pool (110) to any one of a plurality of trunk lines. Also, although remote switch 112 is shown as a PSTN switch, the invention is not intended to be so limited. For example, the gateway MSC (106) can be
5 connected via a transmission line to another MSC or switch in system 100 or to a switch in a different cellular system.

In operation, and in accordance with the exemplary embodiment shown in FIGURE 6, a call is made by a cellular subscriber (A) on mobile phone 102, which is to be directed to a fixed telephone (not explicitly shown) of a PSTN subscriber
10 (B). At call setup, the calling party (A) and called party (B) identification information is received by base station transceiver 104, as part of a call control message using a standard air interface call control message protocol. This information is coupled to the gateway MSC 106 and analyzed by the traffic control subsystem 108. Once the called party (B) has been identified, the traffic control
15 subsystem (108) conducts a route analysis and associates that called party with a specific route (e.g., from switch to switch) via a trunk line to that party's location.

In this embodiment, the traffic control subsystem (108) determines that the specific trunk route to follow to subscriber B is via the trunk line from exchange terminal circuit 111 to remote switch 112. Once that specific trunk route has been
20 identified, the traffic control subsystem (108) accesses a database (not explicitly shown) and retrieves pertinent transmission characteristics (e.g. predefined by a system operator) about that route. That route information includes, at a minimum, a "flag" or data field that contains known echo path characteristics for that route. The traffic control system can thereby predetermine the precise echo path
25 characteristics of the trunk route that will be used to complete the call.

Depending on the echo path delay characteristics of the trunk route involved, the trunk signalling subsystem 113 can select an echo canceller device (not explicitly shown) from the echo canceller pool (110) to be inserted into that trunk, in order to handle that echo path delay. Notably, in accordance with the present invention, the
30 trunk signalling subsystem also selects the echo cancellation parameters to be used in the echo canceller device selected for that particular route. The parameters used

- 8 -

can be the typical default values provided for all of the echo canceller devices in the pool, or more importantly, they can be individualized parameters designed more precisely for the specific trunk route involved. For this embodiment, the echo canceller pool (110) can be an ECP 303/404 product manufactured by Ericsson Telecom AB. The echo canceller device used can be a type C Echo Canceller, as specified by the International Telecommunications Union (ITU) in ITU-T Recommendation G.165, March 1993, entitled "Echo Cancellers". Using the individualized echo cancellation parameter settings for the specific route involved, the traffic control subsystem (108) and trunk signalling subsystem (113) thereby function to complete a significantly improved speech quality connection between cellular subscriber A and PSTN subscriber B, as compared to prior systems.

FIGURE 7 is a flow chart that illustrates a method that can be used to implement dynamic selection of an echo canceller and individualized echo cancellation parameters for a specific route, in accordance with the preferred embodiment of the present invention. Preferably, a predetermined percentage of the echo cancellers in the pool are defined (e.g., by a system operator) as belonging to a dedicated pool. The remaining echo cancellers, which are not allocated to the dedicated pool, are defined as belonging to a main pool. The use of a dedicated pool of echo cancellers makes it possible for an operator to allow only high priority trunk routes the use of echo cancellers from the dedicated pool. Consequently, if all of the echo cancellers in the main pool are being used, there are still echo cancellers available from the dedicated pool for use in the high priority routes.

For this embodiment, assume that the specific outgoing, long distance trunk (T-ROUTE, n) from gateway MSC 106 to remote switch 112 has been "flagged" as requiring individually defined parameter settings for an echo canceller to be selected and used from the pool (110). Although there are a number of echo cancellation parameters that may be selected (e.g., end path delay, non-linear processor mode, tone disable mode, pulse code modulation encoder law, etc.) for a specific trunk route, the method described herein only illustrates the use of individualized end path delay settings for the specific outgoing trunk route shown in FIGURE 6. However, it should be understood that the method of FIGURE 7 can also be applied for any

- 9 -

trunk route in FIGURE 6 and any or all of the possible echo canceller parameters. Examples of echo canceller parameters and values that can be set for any trunk route are shown in the table of FIGURE 8. As such, an operator can specify any or all of the echo canceller parameter settings for each outgoing route, and thereby
5 significantly improve the overall speech quality of the telephony system.

For this illustrative embodiment, it may be assumed that an operator desires to set the specific echo cancellation parameter "end path delay" to 128 ms for the particular T-ROUTE shown in FIGURE 6. However, setting the "end path delay" parameter to 128 ms actually functions to set the "length" of an adaptive Finite-
10 Impulse-Response (FIR) filter to 128 ms, in the echo canceller that will be selected from the pool (110).

Returning to FIGURE 7, at step 202, a system operator inputs appropriate commands to specify and store in a memory storage location (e.g., relational database) the specific echo cancellation characteristics needed for any or all trunk
15 routes (from the gateway switch to the next respective switch) in the system. In the preferred embodiment, such commands can be made by using, for example, a set of Man-Machine Language (MML) commands. At step 204, an operator defines and stores (e.g., in the relational database) as data transcripts for the system's trunk signalling subsystem (e.g., TSS 113), a set of individual parameters for the specific
20 echo cancellation characteristics specified in step 202. At step 206, an operator defines and stores as data transcripts for the system's traffic control subsystem (e.g., TCS 108), information which specifies that the specific T-ROUTE involved can use the individual parameter set defined and stored for that route.

At step 208, an operator determines whether or not enough echo cancellers
25 are available in the pool (110) to handle traffic via the specific T-ROUTE involved. At step 210, depending on whether or not enough echo cancellers are available in the pool, the operator inputs as data transcripts for the trunk signalling subsystem information that will either decrease or increase an already created dedicated pool. At step 212, the operator inputs as data transcripts for the traffic control subsystem
30 information to allow the specific T-ROUTE involved to use an echo canceller from the dedicated pool.

- 10 -

At step 214, at the onset of a call from subscriber A to PSTN subscriber B, the traffic control subsystem performs a standard call setup procedure and route analysis. At step 216, based on the results of the route analysis performed, the traffic control subsystem determines whether or not an echo canceller pool is needed to cancel echo on the T-ROUTE involved. If not (e.g., a trunk echo canceller is already being used), at step 218, the connection can be made between subscriber A and B without using an echo canceller from the pool, and the present method can be terminated (220). If, however, at step 216, the traffic control subsystem determines that an echo canceller from the pool is needed for the T-ROUTE involved, then at step 222, both the traffic control subsystem and trunk signalling subsystem determine whether or not the specific T-ROUTE involved is allowed to use the dedicated pool (e.g., based on the priority level afforded to that T-ROUTE). If so, as in this illustration, at step 224, the trunk signalling subsystem selects an echo canceller from the dedicated pool. Otherwise, if the T-ROUTE involved has been afforded no particular priority of use, the trunk signalling subsystem selects an echo canceller from the main pool (226).

At step 228, the trunk signalling subsystem determines whether or not the T-ROUTE involved has been defined as a user of individual parameter settings. If so (as in this illustration), at step 230, the trunk signalling subsystem downloads the predefined individual parameters (e.g., 128 ms echo path delay) to the echo canceller device selected from the dedicated or main pool (step 224 or 226), which can be employed under the control of a digital processor, such as, for example, a Digital Signal Processor (DSP) manufactured by Texas Instruments Incorporated. Otherwise, at step 232, the trunk signalling subsystem downloads the default parameters to the echo canceller device selected from the pool.

At step 234, the trunk signalling subsystem enables operation of the echo canceller selected from the dedicated or main pool, along with the individualized echo cancellation parameters, on the specific T-ROUTE involved. At step 236, for the duration of the call, the trunk signalling subsystem mediates the two-way traffic between subscriber A and PSTN subscriber B via the specific T-ROUTE involved. When the call is terminated, at step 238, the traffic control subsystem disconnects

-11-

the call. At step 240, the traffic control subsystem and trunk signalling subsystem disconnect the echo canceller device from the T-ROUTE involved, and at step 242, the trunk signalling subsystem returns that device to the respective dedicated or main pool. The method of dynamically selecting an echo canceller from a dedicated
5 or main pool and operating it with optimal echo cancellation parameter settings tailored for the specific trunk route involved is then terminated (244).

Although a preferred embodiment of the method and apparatus of the present invention has been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited
10 to the embodiment disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the invention as set forth and defined by the following claims.

- 12 -

WHAT IS CLAIMED IS:

1. A method for improving the quality of speech traffic in a telephony system, comprising the steps of:
 - determining an identity of a transmission route to be used for routing said
 - 5 speech traffic in said telephony system;
 - selecting an echo canceller from a plurality of echo cancellers;
 - selecting an echo cancellation parameter from a plurality of echo cancellation parameters, said echo cancellation parameter associated with said transmission route;
 - transferring said echo cancellation parameter to said echo canceller, said echo
 - 10 canceller thereby operating responsive to said echo cancellation parameter; and
 - coupling said echo canceller to said transmission route.
2. The method of Claim 1, wherein said echo cancellation parameter comprises an end path delay.
- 15 3. The method of Claim 1, wherein said echo cancellation parameter comprises a "length" of an adaptive Finite-Impulse-Response filter.
4. The method of Claim 1, wherein said echo cancellation parameter
- 20 comprises a PCM encoder law type.
5. The method of Claim 4, wherein said echo cancellation parameter comprises a PCM encoder A-law.
- 25 6. The method of Claim 4, wherein said echo cancellation parameter comprises a PCM encoder Mu-law.
7. The method of Claim 1, wherein said echo cancellation parameter comprises a non linear processor mode of "off", without hearing comfort.
- 30

-13-

8. The method of Claim 1, wherein said echo cancellation parameter comprises a non linear processor mode of "on", without hearing comfort.

5 9. The method of Claim 1, wherein said echo cancellation parameter comprises a non linear processor mode of "off", with hearing comfort.

10 10. The method of Claim 1, wherein said echo cancellation parameter comprises a tone disabler mode of "off".

11. The method of Claim 1, wherein said echo cancellation parameter comprises an echo suppressor mode of "on".

12. The method of Claim 1, wherein said echo cancellation parameter comprises an echo canceller mode of "on".

15 13. The method of Claim 1, wherein said transmission route comprises a trunk line.

14. The method of Claim 1, wherein said plurality of echo cancellers comprises a main pool of echo cancellers.

15 15. The method of Claim 1, wherein said plurality of echo cancellers comprises a dedicated pool of echo cancellers.

25 16. The method of Claim 13, wherein said transmission route comprises a prioritized transmission route.

17. The method of Claim 1, wherein said telephony system comprises a cellular communications system.

30

-14-

18. The method of Claim 1, wherein said telephony system comprises a satellite communications system.

19. The method of Claim 1, wherein said telephony system includes a
5 Public Switched Telephone Network.

20. An apparatus for use in improving the quality of speech traffic in a telephony system, comprising:

10 an electronic switch for routing said speech traffic over a transmission route in said telephony system;

means coupled to said electronic switch, for selecting an echo canceller from a pool of echo cancellers;

means for selecting an echo cancellation parameter from a plurality of echo cancellation parameters associated with said transmission route;

15 means for transferring said echo cancellation parameter to said echo canceller; and

means associated with said electronic switch, for coupling said echo canceller to said transmission route.

20 21. The apparatus of Claim 20, wherein said echo cancellation parameter comprises an end path delay.

22. The apparatus of Claim 20, wherein said echo cancellation parameter comprises a "length" of an adaptive Finite-Impulse-Response filter.

25 23. The apparatus of Claim 20, wherein said transmission route comprises a trunk line.

24. The apparatus of Claim 20, wherein said pool of echo cancellers
30 comprises a dedicated pool of echo cancellers.

- 15 -

25. The apparatus of Claim 23, wherein said transmission route comprises a prioritized transmission route.

26. The apparatus of Claim 20, wherein said telephony system comprises
5 a cellular communications system.

27. The apparatus of Claim 20, wherein said telephony system comprises a satellite communications system.

10 28. The apparatus of Claim 20, wherein said telephony system includes a Public Switched Telephone Network.

1 / 8

FIG.1






FIG.2



3 / 8

FIG.3



4 / 8

FIG.4




FIG.5





FIG. 6



7 / 8

FIG.7




FIG.8

Parameters	Modes and values possible to set by command
End path delay	<div> <div> 16 ms 32 ms 64 ms 72 ms 80 ms 88 ms 96 ms 104 ms 112 ms 120 ms 128 ms </div> <div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> </div> <div> FIR Filter length Filter length (=64 ms) + Pure delay (step 8 ms) </div> </div>
Non Linear Processor	<ul style="list-style-type: none"> * OFF, canceller only * ON, no noise injection * ON, noise injection
Tone Disabler Mode	<ul style="list-style-type: none"> * OFF * ON, according to ITU-T G.164 * ON, according to ITU-T G.165
PCM encoder law	<ul style="list-style-type: none"> * A-law * Mu-law

INTERNATIONAL SEARCH REPORT

International Application No

PCT/SE 98/00060

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04B3/23

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04B H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 017, no. 421 (E-1409), 5 August 1993 & JP 05 083753 A (NEC CORP), 2 April 1993, see abstract ---	1,20
A	WO 93 09610 A (NOKIA TELECOMMUNICATIONS OY) 13 May 1993 see page 2, line 4 - line 35 see page 3, line 25 - line 32 see page 4, line 4 - line 18 ---	1,20
A	PATENT ABSTRACTS OF JAPAN vol. 095, no. 002, 31 March 1995 & JP 06 315046 A (NIPPON TELEGR & TELEPH CORP), 8 November 1994, see abstract ---	2,21
-/--		



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

8 July 1998

Date of mailing of the international search report

15/07/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Larcinese, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/SE 98/00060

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 333 195 A (BOWKER DUANE O ET AL) 26 July 1994 see column 5, line 18 - line 30 -----	4-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SE 98/00060

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9309610	A	13-05-1993	FI 915201 A	05-05-1993
			AT 148282 T	15-02-1997
			AU 657814 B	23-03-1995
			AU 2888792 A	07-06-1993
			DE 69217042 D	06-03-1997
			DE 69217042 T	19-06-1997
			EP 0565687 A	20-10-1993
			JP 6503700 T	21-04-1994
			US 5450487 A	12-09-1995
US 5333195	A	26-07-1994	US 5195132 A	16-03-1993
			AU 632005 B	10-12-1992
			AU 8788591 A	04-06-1992
			CA 2052253 A,C	04-06-1992
			EP 0489543 A	10-06-1992
			JP 2625301 B	02-07-1997
			JP 4287523 A	13-10-1992